	*			JOUR RECUPCION 2 7 FEB 2		
FORM P	TO390 -98)	0 (Modified) U.S. DEPARTME	ENT OF COMMERCE PATENT AND TRADEMARK OFFICE	ATTORNEY'S DOCKET NUMBER		
		RANSMITTAL LETTE	6001-011			
		DESIGNATED/ELEC	U.S APPLICATION NO. (IF KNOWN, SEE 37 CFR			
		CONCERNING A FILI	To Be Assigned / 763723			
INTER	RNATI	IONAL APPLICATION NO. PCT/EP99/06272	INTERNATIONAL FILING DATE 26-August-1999	PRIORITY DATE CLAIMED  27-August-1998		
TITLE		NVENTION	av rangust 1777	ar rangustario		
Polyı	merio	e Films				
		T(S) FOR DO/EO/US				
RMI	MSC	OMBE				
∆ nn¹:	cant 1	erewith submits to the II-it- 1	States Designated/Elected Office (DO/EO/US)	the following items and other information		
			,	· ·		
1.			of items concerning a filing under 35 U.S.C. 37			
2.			EQUENT submission of items concerning a fil	<del>-</del>		
3.		into its an express request to be examination until the expiration	begin national examination procedures (35 U.S. on of the applicable time limit set in 35 U.S.C.	.C. 3/1(t)) at any time rather than delay 371(b) and PCT Articles 22 and 39(1).		
4.	$\boxtimes$	<u>-</u>		he 19th month from the earliest claimed priority date.		
5.	$\boxtimes$	A copy of the International A	pplication as filed (35 U.S.C. 371 (c) (2))	· · · · · · · · · · · · · · · · · · ·		
		a.   is transmitted herew.	ith (required only if not transmitted by the Inte	ernational Bureau).		
•		b. 🛭 has been transmitted	by the International Bureau.			
		c. $\square$ is not required, as the	e application was filed in the United States Red	ceiving Office (RO/US).		
6.		A translation of the Internatio	nal Application into English (35 U.S.C. 371(c)	)(2)).		
7.	$\boxtimes$	A copy of the International Se	earch Report (PCT/ISA/210).			
8.		Amendments to the claims of	the International Application under PCT Artic	le 19 (35 U.S.C. 371 (c)(3))		
•		a.   are transmitted herev	with (required only if not transmitted by the Int	ternational Bureau).		
1		b.   have been transmitted.	ed by the International Bureau.			
			; however, the time limit for making such amer	ndments has NOT expired.		
ĺ			and will not be made.			
<b>¥</b> 9.			ents to the claims under PCT Article 19 (35 U.S	S.C. 371(c)(3)).		
10.	$\boxtimes$		inventor(s) (35 U.S.C. 371 (c)(4)).			
11.	$\boxtimes$	A copy of the International Preliminary Examination Report (PCT/IPEA/409).				
12.		A translation of the annexes to (35 U.S.C. 371 (c)(5)).	o the International Preliminary Examination Ro	eport under PCT Article 36		
Ĭŧ	ems 1		nent(s) or information included:			
13.			statement under 37 CFR 1.97 and 1.98.			
14.	$\boxtimes$		recording. A separate cover sheet in complian-	ce with 37 CFR 3.28 and 3.31 is included.		
15.	$\boxtimes$	A FIRST preliminary amend				
16.		A SECOND or SUBSEQUE				
17.		A substitute specification.	•			
18.		A change of power of attorne	y and/or address letter.			
19.		Certificate of Mailing by Exp				
20.	$\boxtimes$	Other items or information:				
		1. Copy of Application as P	Published Under the PCT, Publ. No. WO 00/	12288;		
		2. Form PTO-1449 with co				
1		3. Copy of Form PCT/IB/36 4. Copy of PCT Request Fo				
Ī		5. Postcard.				

The list of the second second of the second second

U.S. APP	LICATION	NO. (IF KNOW Se Assigne	VN, SEI	E 37 CER	INTERNATIONAL A PCT/EP					DOCKET NUMBER 1-011#
21					TCI/EI	JJ10021			<b>.</b>	•
21.		lowing fees and L FEE ( 37 C			(5)) •				CALCULATIONS	PTO USE ONLY
☐ N ii	Neither international	national preli search fee (3	minary 7 CFR	examination 1.445(a)(2)	n fee (37 CFR 1.482) no paid to USPTO by the EPO or JPO		\$97	0.00		
Z I							0.00			
□ I	_									
□ I: b	nternational out all claims	preliminary of satis	examin	ation fee pai	d to USPTO (37 CFR 17 Article 33(1)-(4)	1.482)	\$67	0.00		
□ I a	nternational nd all claim	preliminary of satisfied pro	examin ovision	ation fee pai s of PCT Ar	d to USPTO (37 CFR 1 ticle 33(1)-(4)	1.482)	\$9	6.00		
		ENTE	R AP	PROPRI	ATE BASIC FE		OUNT =		\$840.00	
Surcharg months	ge of <b>\$130.0</b> from the ear	<b>0</b> for furnishiliest claimed	ng the priority	oath or decla y date (37 C	aration later than FR 1.492 (e)).	□ 20	) 🗆 3	O	\$0.00	
CLA	IMS	NUM	(BER I	FILED	NUMBER EXT	RA	RATE	3		
Total cla	iims		11	- 20 =	0		x \$18.0	0	\$0.00	
Indepen	dent claims		2	- 3 =	0		x \$78.0	0	\$0.00	
Multipl	e Dependen	t Claims (che							\$0.00	
			TC	TAL OF	ABOVE CALC	ULAT	IONS	=	\$840.00	
Reduction must als	on of 1/2 for o be filed (1	filing by sm Note 37 CFR	nall ent 1.9, 1.	ity, if applica 27, 1.28) <b>(ch</b>	ible. Verified Small Eneck if applicable).	ntity Stat	ement		\$0.00	
						SUB	TOTAL	=	\$840.00	
Processi months	ng fee of \$1 from the ear	30.00 for fur liest claimed	nishing priorit	g the English y date (37 C	translation later than FR 1.492 (f)).	□ 20	0 🗆 3	0 +	\$0.00	
		,			TOTAL NAT	IONAI	L FEE	=	\$840.00	
Fee for accompa	recording the	e enclosed as appropriate c	signme over sh	ent (37 CFR neet (37 CFR	1.21(h)). The assignme 3.28, 3.31) (check if a	ent must l applicabl	oe le).	×	\$40.00	
					TOTAL FEES	ENCL	OSED	=	\$880.00	
									Amount to be: refunded	\$
									charged	\$
□ A check in the amount of \$880.00 to cover the above fees is enclosed.      □ Please charge my Deposit Account No. in the amount of to cover the above fees.										
⊠ NOTE:	The Comm to Deposit.  Where an	Account No.	reby au 50 time l	uthorized to o  0-0622  imit under 3	charge any fees which in A duplicate copy of the Grant 1.494 or 1.495	is sheet i	s enclosed.			R
1.137(a) or (b)) must be filed and granted to restore the application to pending status.										
SEND ALL CORRESPONDENCE TO:  SHANKS & HERBERT  STONATURE										
TransPotomac Plaza 1033 North Fairfax Street, Suite 306 Alexandria, Virginia 22314 (703) 683-3600 (703) 683-9875 (facsimile)						David W. Woodward  NAME				
(703) (	085-9875 (fa	icsimile)					35,020			
							REGIST	RATI	ON NUMBER	
27-February-2001										
DATE										
1						l				

09/763723 JC02 Rec'd PCT/PTO 2 7 FEB 2001

## IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of: BIDDISCOMBE

Art Unit: To Be Assigned

Serial No.: To Be Assigned

Examiner: To Be Assigned

Filed: Herewith

Atty. Docket: 6001-0111

For: Polymeric Films

#### PRELIMINARY AMENDMENT

Assistant Commissioner for Patents Washington, D.C. 20231

Sir:

Prior to examination of the above-identified application, Applicant herewith respectfully requests the following amendments:

### IN THE CLAIMS:

- 3. An article according to [either of the preceding] claim[s] 1, wherein the shrinkage of the film in the transverse direction is at least 6%.
- 4. An article according to [any of the preceding] claim[s] 1, wherein the shrinkage of the film in the machine direction is at least 5%.
- 5. An article according to [any of the preceding] claim[s] 1, wherein the shrinkage of the film in the machine direction is at least 6%.
- 6. An article according to [any of the preceding] claim[s] 1, wherein the film comprises a polypropylene homopolymer base layer with at least one outer layer thereon.

- 8. An article according to claim 6 [or claim 7], wherein the base layer contains a hydrogenated hydrocarbon resin.
- 9. An article according to [any of the preceding] claim[s] 1, wherein the film comprises a base layer comprising a propylene homopolymer, at least one intermediate intermediate polyolefin layer on the base layer, and an outer layer on the intermediate layer.

# REMARKS

It is respectfully requested that the Examiner enter these amendments prior to examining the application on its merits.

Respectfully submitted,

SHANKS & HERBERT

By: Wilsahan/

David W. Woodward Reg. No. 35,020

Date: Telmy 27 201

TransPotomac Plaza 1033 N. Fairfax Street Suite 306 Alexandria, VA 22314 (703) 683-3600 WO 00/12288

- 1 -

# Polymeric Films

This invention concerns polymeric films and in particular the use of such films for the in-mold labelling of articles.

The in-mold labelling of articles, in which a label is incorporated into the surface of an article made from a polymeric material as the article is formed, is a well known technique. Many proposals have therefore been made concerning materials which can be used to form the articles, the materials of which the labels are formed, and the processing conditions under which the articles are formed and therefore labelling itself is effected.

Important factors in achieving satisfactory in-mold labelling are the ability of the label to adhere to the article which is being produced, and also the ability of the label to withstand the processing conditions which are encountered during the formation of the article itself. More particularly, in-mold labelling usually involves subjecting the labels to elevated

temperatures for significant periods of time, this being particularly so with blow in-mold labelling where a polymeric parison is heated to a temperature at which it can be blown into the internal shape of a mold into which a label has previously been placed.

Using polyolefinic parisons, the labels used will themselves usually be formed from polyolefins, polypropylene and polyethylene being widely used as parison materials. Typically films used for the in-mold labelling of polyolefinic parisons are also made from polyolefins, polypropylene based films being widely proposed as being suitable for use in labelling articles made by blow molding either polypropylene or polyethylene parisons.

Typical of the problems encountered using polymeric films as labels for application to articles formed by in-mold blowing of polyolefin parisons using polyolefin films as labels are poor adhesion of the label to the articles, which can be manifest as blisters under the labels, and/or undesirable effects on the labels themselves caused by the heat to which the polymeric films are subjected during formation of the articles, for example distortion and "orange peel" effects.

Many proposals have been made for overcoming such disadvantages, these usually depending on the nature of the polyolefin from which the parisons are made. It should also be appreciated that whereas little or no problems may be encountered using a particular polyolefin film to effect blow in-mold labelling of articles made from parisons of one polyolefin, the same film can suffer the disadvantages referred to above when used in blow in-mold labelling of articles made from parisons of another polyolefin. For example, if conventionally produced films consisting of either a solid or a voided polypropylene homopolymer core layer with two outer layers of a heat sealable propylene ethylene copolymer are used as in-mold labels for articles produced from polypropylene homopolymer parisons, satisfactory adhesion of the label to the article can, in

 general, be readily achieved. However, if the same film is used for the blow in-mold labelling of high density polyethylene articles, blistering and/or "orange peel" effects are obtained.

Hitherto proposed methods of overcoming such problems include the provision of layers in the label films themselves which have been suggested compensate for changes in the dimensions of the labels as a result of the heat applied to them by the heated parison, such layers being formed, for example, from foamed or voided polyolefins.

It has also been proposed to use adhesive layers to improve bonding of the labels to the articles. However, the use of such materials complicates production of the films used to produce the labels and it increases their cost.

It has also been proposed that films used to form labels for in-mold labelling should be as dimensionally stable as possible during the in-mold labelling process, which in effect means that as far as possible the films should not shrink during the in-mold labelling process.

According to the present invention there is provided an in-mold labelled, blow-molded article formed from high density polyethylene, the label being formed from a biaxially oriented polypropylene based film having a shrinkage of at least 4% in both the machine and transverse directions as measured by the OPMA shrink test in which the film is suspended in an oven at 130°C for a period of 10 minutes.

Despite the widely held belief in the art that labels for in-mold labelling should have the minimum possible shrinkage when subjected to the temperatures to which they are subjected during in-mold labelling, the present invention is based on the use of films which shrink significantly at such temperatures. The minimum shrinkage in either the machine or transverse direction of the films should be at least 4% as measured by the OPMA shrink test. However, the shrinkages can be more. For

the built of the first than the first the first than the second of the first that

example, the machine direction shrinkage can be at least 5%, more particularly at least 6%, and as much as 7% or more, for example more than 8%. The transverse direction shrinkages can, for example, be at least 5%, more particularly at least 6%, and as much as 7% or more, for example more than 8%.

It is particularly surprising that both blistering and "orange peel" effects can be avoided by the use of films having shrinkages of greater than 4% as measured by the OPMA shrink test in both the machine and transverse directions. Furthermore, this surprising effect is observed both with polyolefin homopolymer based films having densities of not more than 0.69g/cm<sup>3</sup>, that is voided films, where "orange peel" effects have been a problem with films with shrinkages of less than 4%, and with films with densities of 0.8g/cm<sup>3</sup> or more, where blister formation tends to occur with prior art films.

Films used for in-mold labelling in accordance with the present invention can have any of a wide variety of structures provided they have the required degree of shrinkage. However, they preferably have one or more layers of a propylene homopolymer with at least one outer layer of a heat sealable polymer, the heat sealable polymer being positioned next to the high density polyethylene when the article is blow molded so that the film adheres to the polyethylene of the article. Examples of heat sealable polymers which can be used include copolymers derived from two or more of ethylene, propylene, butene-1 and higher molecular weight a-olefins. Particularly preferred are copolymers of ethylene and propylene, and of ethylene, propylene and butene-1, such polymers preferably containing a major amount of units derived from propylene. When two heat sealable outer layers are present, they can be formed from the same or different polymeric materials.

In addition to at least one outer layer, the films can include at least one intermediate layer, the intermediate layer or layers preferably being formed from at least one polyolefin which can be a homopolymer but is preferably a copolymer derived from at least two different types of  $\alpha$ -olefin and/or ethylene.

When an outer layer is present, the base layer and/or any intermediate layer which may be present preferably contains a hydrogenated hydrocarbon resin, it having been proposed hitherto to use such resins to increase the heat shrinkability of polyolefin films.

The polypropylene homopolymer layer or layers can contain a filler, and such fillers can act as a pigment which serves to opacify the layer or layers in which they are present, for example sub-micronic titanium dioxide, and/or they can act as a voiding agent, for example organic or inorganic fillers having particle sizes of at least 1µm, e.g. particulate chalk and polymeric particles such as those formed from polyamides and polyesters.

When a filler is used which induces voiding, the films will usually have densities less than that for polypropylene homopolymers, for example less than  $0.9g/cm^3$ , and often less than  $0.69g/cm^3$ .

Films used as in-mold labels in accordance with the present invention will can contain additives used in the polymeric film art. Thus they will usually include an antiblock agent in one or both outer surfaces of the films, for example silica or a particulate polyamide, e.g. a nylon. Other additives can also be present in one or more of the layers, for example slip and antistatic agents. Examples of slip agents which can be present include long chain fatty acid amides, e.g. erucamide, and glycerol mono-esters of long chain fatty acids, e.g. glycerol monostearate. Examples of antistatic agents which can be used include polyethoxylated aliphatic amines such as bis-ethoxylated long chain aliphatic amines.

Films used in accordance with the present invention to form labels for blow molded articles can in essence be produced by

known methods, subject to steps being taken to provide them with shrinkages in both the machine and transverse directions of at least 4%. Thus they will in general be produced by coextrusion of melts of the appropriate compositions through a die following which the coextrudate is biaxially oriented.

The biaxial orientation of the films can be effected either simultaneously, for example using the so-called "bubble" process, or sequentially, for example using heated rollers with different peripheral speeds to stretch the films in the direction of extrusion, and then using a stenter oven in which the films are stretched in the transverse direction. However, sequential stretching is generally preferred for reasons which will be explained.

In order to impart the desired degree of shrinkage to the films which are used in accordance with the present invention, it is important to anneal them at lower temperatures than are normally used to produce heat sealable packaging films. More particularly, it is generally preferred to effect sequential stretching of the films so that two annealing steps can be effected, the first after stretching of the films in the machine direction, and then a second after the films have been stretched in the transverse direction, this enabling greater control to be exercised over the respective degrees of shrinkage in the machine and transverse directions. Hence the preference for sequential rather simultaneous stretching, apart from the problems with the latter in producing films including voids in one or more of their layers.

Biaxial stretching of the films used in accordance with the present invention is preferably effected by a factor of from 3.5 to 7:1 in the machine direction and by from 5 to 10:1 in the transverse direction.

Annealing of the films following their being stretched in the machine direction is preferably effected at a temperature of less than 112°C, compared with conventional temperatures in

, 7h

excess of 115°C, this annealing being more preferably effected at temperatures of less than 105°C, and advantageously less than 100°C, particularly high shrinkages having been achieved at annealing temperatures of about 97°C following stretching of the films in the machine direction, for example at temperatures of about 116°C. Annealing of the films in the machine direction is preferably effected by passing them over the surface of a plurality of rollers each with outer surfaces at the desired annealing temperature, the rollers each having substantially the same peripheral speeds so that the stretched length of the films in the machine direction is substantially maintained during the annealing process, i.e. there is substantially no stretching or relaxation of the film in the machine direction during the annealing process.

Annealing of the films following their being stretched in the transverse direction is preferably effected at a temperature of less than 145°C, compared with conventional temperatures of about 150C, this annealing being more preferably effected at temperatures of less than 140°C, and advantageously less than 130°C, particularly high shrinkages in the transverse direction having been achieved at annealing temperatures of less than 120°C, and especially less than 120°C following stretching of the films in the machine direction, for example at temperatures of less than 115°C, such as 105°C. Annealing of the films in the transverse direction is preferably effected by passing them over the surface of a number of rollers with outer surfaces at the desired annealing temperature whilst substantially maintaining the stretched width of the films, i.e. it is preferred that there is substantially no stretching or relaxation of the films in the transverse direction during the annealing process.

Once the films have been annealed following their having been biaxially stretched, at least one surface is preferably treated to increase its surface energy, for example by flame or corona discharge treatment, following which it is wound up.

The films can then be printed and cut to the shape and size required for the subsequent blow in-mold labelling process which can be effected in known manner.

Films used as labels in accordance with the present invention can be of a variety of thicknesses, but in general they should be at least 60 $\mu$ m thick to facilitate processing in the in-mold labelling process itself. However, the films will not usually be more than 120 $\mu$ m thick due to mechanical constraints in the formation of biaxially stretched films of such thicknesses.

The following Examples are given by way of illustration only.

## Example 1

A three layer polymeric web was by coextruding through a slot die a core layer consisting of a propylene homopolymer containing 6wt% of titanium dioxide with a mean particle size of less than 1µm as a pigment and 2.1wt% of chalk with a mean particle size of 3µm as a voiding agent, with two outer layers each consisting of a propylene/ethylene copolymer (4wt% ethylene) on the surface of the core layer.

The web was cooled and it was then stretched 4.5 times in the direction of extrusion by passing it over heated rollers with differing peripheral speeds, the rollers being heated to a temperature of 116°C. The stretched film was then annealed by passing it over a series of annealing rollers with peripheral speeds substantially the same as that of the last of the rollers effecting stretching in the machine direction, the temperature of these annealing rollers being 97°C.

The mono-axially stretched web was then stretched 8 times in the transverse direction using a stenter oven at a temperature of 159°C, following which it was annealed at a temperature of 105°C with substantially no change in the width of the film.

Thereafter, the film was corona discharge treated on the first outer layer and wound up. The film had a total thickness of 80µm, the copolymer layer being 2.5µm thick, the terpolymer layer being 2µm thick, and the core layer being 76.5µm thick.

The film had a shrinkage in the machine direction of 7.6% and in the transverse direction of 11.4% as measured by the OPMA shrink test in which the film is suspended in an oven at 130°C for a period of 10 minutes. The density of the film was 0.8g/cm<sup>3</sup>.

The film was then cut into labels which were used to label blow molded containers by insertion of the film into the mold before the containers were formed. The labels of the resulting labelled containers showed neither an "orange peel" effect nor blistering.

## Example 2 (comparison)

A three layered polymeric film was produced substantially as described in Example 1 except that annealing in the machine direction was effected at a temperature of 116°C and in the transverse direction it was effected at a temperature of 150°C.

The film, which had layer thicknesses and a total thickness as given in Example 1, had a shrinkage of 4% in the machine direction and 0.7% in the transverse direction. The density of the film was  $0.8g/cm^3$ .

When used for in-mold labelling under substantially the same conditions used for the film of Example 1, blisters were noticed under the label even though there was no "orange peel" effect.

#### Claims

- 1. An in-mold labelled, blow-molded article formed from high density polyethylene, the label being formed from a biaxially oriented polypropylene based film having a shrinkage of at least 4% in both the machine and transverse directions as measured by the OPMA shrink test in which the film is suspended in an oven at 130°C for a period of 10 minutes.
- 2. An article according to claim 1, wherein the shrinkage of the film in the transverse direction is at least 5%.
- 3. An article according to either of the preceding claims, wherein the shrinkage of the film in the transverse direction is at least 6%.
- 4. An article according to any of the preceding claims, wherein the shrinkage of the film in the machine direction is at least 5%.
- 5. An article according to any of the preceding claims, wherein the shrinkage of the film in the machine direction is at least 6%.
- 6. An article according to any of the preceding claims, wherein the film comprises a polypropylene homopolymer base layer with at least one outer layer thereon.
- 7. An article according to claim 6, wherein the outer layer or layers comprises a heat sealable polymer.
- 8. An article according to claim 6 or claim 7, wherein the base layer contains a hydrogenated hydrocarbon resin.
- 9. An article according to any of the preceding claims, wherein the film comprises a base layer comprising a propylene homopolymer, at least one intermediate polyolefin layer on the base layer, and an outer layer on the intermediate layer.

- 10. An article according to claim 9, wherein the base layer and/or the intermediate layer contains a hydrogenated hydrocarbon resin.
- 11. An-mold labelled, blow-molded article substantially as herein described with reference to Example 1.

#### COMBINED DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below, next to my name. I believe I am the original, first, and sole inventor (if only one name is listed below) or an original, first, and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled <u>Polymeric Films</u> the specification of which:

_X_	is attached hereto.
	was filed on
	as United States Application Number
	or PCT International Application Number
	and was amended on
	(if applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claim(s), as amended by any amendment referred to above. I do not know and do not believe that the claimed invention was ever known or used in the United States of America before my invention thereof, or patented or described in any printed publication in any country before my invention thereof or more than one year prior to this application, that the same was not in public use or on sale in the United States of America more than one year prior to this application, and that the invention has not been patented or made the subject of an inventor's certificate issued before the date of this application in any country foreign to the United States of America on an application filed by me or my legal representatives or assigns more than twelve months (for a utility patent application) or six months (for a design patent application) prior to this application.

I acknowledge the duty to disclose all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119(a)-(d), of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Applica	tion(s)		Priority <u>Claimed</u>	<u>d</u>
9818560.6 (Number)	GB (Country)	27-August-1998 (Day/Month/Year Filed)	X Yes	No
PCT/EP99/06272 (Number)	WO (Country)	26-August-1999 (Day/Month/Year Filed)	X Yes	No
(Number)	(Country)	(Day/Month/Year Filed)	Yes	No
l hereby claim the be provisional applicatio		Inited States Code, Section 119(e) o	of any Unite	ed States
(Application Number)		Filing Date		

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, Section 112, I acknowledge the duty to disclose all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Number)	Filing Date	(Status – patented, pending, abandoned)
(Application Number)	Filing Date	(Status – patented, pending, abandoned)
(Application Number)	Filing Date	(Status - patented, pending, abandoned)

I hereby appoint Toni-Junell Herbert, Registration No. 34,348, Mark R. Shanks, Registration No. 33,781, David W. Woodward, Registration No. 35,020, Keith D. Hutchinson, Registration No. 43,687, Joseph G. Contrera, Registration No. 44,628, Chalin A. Smith, Registration No. 41,569, Shelly Guest Cermak, Registration No. 39,571, Suzannah K. Sundby, Registration No. 43,172, of SHANKS & HERBERT, telephone (703) 683-3600, with a mailing address at:

TransPotomac Plaza 1033 N. Fairfax St., Suite 306 Alexandria, VA 22314

with full power of substitution and revocation, to prosecute this application and to transact all business in the Patent and Trademark Office connected herewith.

The undersigned hereby authorizes the U.S. Attorneys named herein to accept and follow instructions from undersigned's assignee, if any, and/or, if the undersigned is not a resident of the United States, the undersigned's domestic attorney, patent attorney or patent agent, as to any action to be taken in the Patent and Trademark Office regarding this application without direct communication between the U.S. attorneys and the undersigned. In the event of a change in the person(s) from whom instructions may be taken, the U.S. attorneys named herein will be so notified by the undersigned.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application of any patent issued thereon.

	Full Name of Sole/First Inventor: Helen BIDDISCOMBE
í	(Anventor's Signature: X clabolosse Date: X 1/2/01
/	Residence Bridgwater, Somerset (XBX Citizenship: GB
	(City, State) (Country) Post Office Address: Cherry Grove, Newton Road, North Petherton, Bridgwater, Somerset TA6
	6SN, Great Britain